

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



**ATEX** Ⓢ  
CE Ⓢ II 2GD  
Ex h IIC T6 Gb  
Ex h IIIC T85°C Db

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)




**GUARANTEED** for the Safe Recovery of Combustible/Conductive Dusts

**ATEX** Ⓢ  
ATEX 3rd Party Certified  
CE Ⓢ II 2GD  
Ex h IIC T6 Gb  
Ex h IIIC T85°C Db  
LCIE 03 ATEX 6310 X




EX Certified




Less than 10 ohms



Dry Recovery



Wet Mix - Water



Wet Mix - Oil



HEPA - Included



High Filtration Efficiency Unit



SS 304



Coalescing Filter Element



SD Accessories - Included



3D Printing

## Specifications For SS-10 (IT-40L) DT RE HEPA W/3D TOOL KIT

| Name                                    | Part Number  | Air Flow              | Vacuum Pressure          |
|---|--|-----------------------|--------------------------|
| SS-10 (IT-40L) DT RE HEPA W/3D TOOL KIT | 113119-3D  | 212 m <sup>3</sup> /h | 2790 mm H <sub>2</sub> O |
|   | Dimensions: H137 cm x W56 cm x L66 cm    Weight: 48 kg.    Sound Level: 72 dB(A) |                       |                          |

Please note that specifications are subject to change without notice

## Technical Sheet For SS-10 (IT-40L) DT RE HEPA W/3D TOOL KIT

| FILTERS - Included |   |
|--------------------|---|
| Part #             | Description   |
| 215792A            | REPLACEMENT COALESCING FILTER ELEMENT 5.88" OD x 3.5" ID x 4.75"HIGH WITH NITRILE GASKET #219259-04 |
| 211027B            | HEPA FILTER 99.995% EFFICIENCY ON 0.3 MICRON (CE VERSION)   |

| MIST ARESTOR PACK - Included |   |
|------------------------------|---|
| Part #                       | Description   |
| 218282                       | MIST ARRESTOR SCREENS, MADE OF ALUMINUM MESH, FOR IT-40L (SET OF 6 SCREENS) |
| 218284                       | MIST ARRESTOR PACK ASSEMBLY (ALUMINUM SCREENS WITH STAINLESS STEEL MESH)    |

| CONDUCTIVE RECOVERY BAG - Included |   |
|------------------------------------|---|
| Part #                             | Description   |
| 219992A                            | CONDUCTIVE RECOVERY BAG FOR IT-40L MINI ENHANCED                |
| 219992                             | CONDUCTIVE RECOVERY BAG FOR IT-40L MINI ENHANCED (PACKAGE OF 3) |

| DEPRESSOR CAGE FOR CONDUCTIVE RECOVERY BAG - Optional |   |
|---|---|
| Part #  | Description   |
| 228093  | DEPRESSOR CAGE FOR CONDUCTIVE WET RECOVERY BAG FOR IT-40L, MADE OF TYPE 304 STAINLESS STEEL |

| TOOLS AND ACCESSORIES - Included |             |
|----------------------------------|-------------|
| Part #                           | Description |

|         |   |
|---------|---|
| 383440  | STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASSEMBLY 1.5"(38mm) x 10'(3m) FOR 1.5" CAMLOCK INTAKE   |
| 211029  | AIR SUPPLY HOSE ASSEMBLY SD* 0.5"(12.7mm) x 25'(7.5m) w/1 MALE QUICK DISC. & 1 FEMALE QUICK DISC. |
| 381818  | CREVICE TOOL 1.5"(38mm) x 8"(20cm) w/1.5" ALUMINUM TUBE, BLACK RUBBER, CONDUCTIVE & OIL RESISTANT |
| 383312A | ROUND BRUSH ASSEMBLY, ESD SAFE PLASTIC, FOR USE WITH 1.5" (38mm) HOSE                             |
| 383462  | CONICAL NOZZLE ASMBLY w/CURVED TIP, 10"(25cm) CONDUCTIVE RUBBER, PRESSURE FIT (323562+381155A-H)  |

#### TOOLS AND ACCESSORIES - Optional

| Part #  | Description   |
|---------|---|
| 381477  | DOUBLE BEND WAND (2pc) 1.5" (38mm) x 54" (137cm), CHROME, w/TAPER FOR PLASTIC FLOOR TOOLS           |
| 381448A | UTILITY FLOOR TOOL, Ø1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES |