



CE EX II 3D
Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X
LCIE 19 ATEX 1001 X



IECEx 3rd Party Certified
Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X
IECEx LCIE 15.0048



This model can be used to Recover Combustible Dusts such as Dust Groups :

- IIIA** Combustible Flyings (lints of cotton, wood chips, etc.)
- IIIB** Non-Conductive Dusts (flour dust, grain dust, flour, sugar, starch, wood, plastic, carbonaceous dusts, coal, carbon black)
- IIIC** Conductive Dusts (combustible metal dust, aluminum, magnesium, commercial alloys)

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.
We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

Characteristics



Static Dissipating



HEPA - Included



High Filtration Efficiency Unit



Stainless General



SD Accessories - Included




Dry Recovery



Detachable Tank



EX Certified



3D Printing



Brushless Motor Available



- Ideal for housekeeping and general cleaning
- Includes 4 HEPA filters. Class H14. Individually factory tested
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 4 x H14 HEPA filters
- Material to be recovered within a conductive poly liner recovery bag for easy disposal
- Equipped with a filter blockage indicator light to know when the recovery bag is full
- Recovery tank made of stainless steel Type 430. Recovery tank made of stainless steel Type 304 is also available
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Includes a complete static dissipative tool kit

Specifications

C-10 EX DT (MFS)	111786B
Model Name	C-10 EX DT (MFS)
Type (Powerhead)	Electric
Tension	220-240 V
Frequency	50/60 Hz
Phase	Single
Wattage	1200 W
Power	1.2 kW
Amperage	5 A
Air Flow	194 m ³ /h
Vacuum Pressure	2504 mm H ₂ O
Sound Level	72 dB(A)
Type of Power Outlet	Not Included
Suction Inlet Port	60 mm
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dust Recovery Tank	25 L
Length	66 cm
Width	66 cm
Height	112 cm
Weight (Vacuum Only)	39.5 kg.
Cord Length	10 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories




Conductive Polyliner Recovery Bag - Included



Main Cloth Filter and Cage, Static Dissipative - Included



C-10EX DT (MFS) Recovery Tank and Poly Liner



C-10EX DT (MFS) Tool Basket



Upstream HEPA Filter - Included



Cable Holder Hook included on the side of the powerhead



Longer Life Brushless Motor Available (always with 4 x H14 HEPA filters)



C-10 EX DT (MFS) Tool Kit - included