

Characteristics



- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- Static free and ESD safe
- EMI/RFI Shielded
- 5-stage filtration system, includes dual ULPA filters (U15) (one for the working air and one for the cooling air), double cloth filter, and disposable filter bags
- Designed for use in contamination controlled environments
- Heavy duty 2-stage by-pass motor
- For wet & dry recovery
- Stainless steel recovery tank
- Mounted on a 4-wheel dolly for easy maneuverability
- Includes a complete tool kit.
- Cable Hook Holder Included
- Drain Valve Assembly Optional



Specifications

| CWR-8 (4W) | 110491B | 110491C | 110491E |
|---|--------------------------|--------------------------|--------------------------|
| Model Name | CWR-8 (4W) | CWR-8 (4W) | CWR-8 (4W) |
| Type (Powerhead) | Electric | Electric | Electric |
| Tension | 240 V | 240 V | 240 V |
| Frequency | 50 Hz | 50 Hz | 50 Hz |
| Phase | Single | Single | Single |
| Wattage | 1050 W | 1050 W | 1050 W |
| Power | 1 kW | 1 kW | 1 kW |
| Amperage | 5 A | 5 A | 5 A |
| Air Flow | 189 m ³ /h | 189 m ³ /h | 189 m ³ /h |
| Vacuum Pressure | 2180 mm H ₂ 0 | 2180 mm H ₂ 0 | 2180 mm H ₂ 0 |
| Sound Level | 75 dB(A) | 75 dB(A) | 75 dB(A) |
| Type of Power Outlet | European | UK | Chinese |
| Suction Inlet Port | 38 mm | 38 mm | 38 mm |
| Cart Type | 4 Wheel Dolly (4W) | 4 Wheel Dolly (4W) | 4 Wheel Dolly (4W) |
| Filter Cleaning | None | None | None |
| Dust Recovery Tank | 24.6 L | 24.6 L | 24.6 L |
| Dry Recovery - Disposable Filter Bag | 9.5 L | 9.5 L | 9.5 L |
| Liquid Recovery Capacity | 24.6 L | 24.6 L | 24.6 L |
| Length | 58 cm | 58 cm | 58 cm |
| Width | 48 cm | 48 cm | 48 cm |
| Height | 76 cm | 76 cm | 76 cm |
| Weight (Vacuum Only) | 23 kg. | 23 kg. | 23 kg. |
| Cord Length | 10.6 m | 10.6 m | 10.6 m |

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



ULPA Filter - Included



Autoclavable Suction Hose and Accessories - Optional



CWR Tools and Accessories - Included



CWR-8 (4W) Cable Holder Hook - Included

Tiger-Vac International Inc. 2020 Dagenais Blvd. Ouest Laval, Quebec Canada H7L 5W2 Tel: ((39) 051 79.53.52) Fax: ((39) 051 4695077)

Website: http://www.tiger-vac.eu Email: info@tiger-vac.it