


Characteristics



Cleanroom
Compatible



Pharma
Applications



ULPA - Included



Stainless
Steel
General



Accessories
Included



Low Noise



Dry Recovery



High Filtration
Efficiency Unit



- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- 3-stage filtration system, includes an ULPA (U15) filter, main cloth filter, and disposable filter bags
- Designed for use in contamination controlled environments
- Thru-Flow heavy duty motor
- Low noise level - only 60 dB(A) at 6.6' (2m)
- For dry recovery only
- Available with a plastic or stainless steel recovery tank
- Mounted on a 4-wheel dolly for easy maneuverability
- Includes a complete tool kit.

Specifications

CR-1 ULPA	110760B	110760BP	110760C	110760CP	110760D	110760DP
Model Name	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
Tension	240 V	240 V	240 V	240 V	240 V	240 V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Phase	Single	Single	Single	Single	Single	Single
Wattage	1000 W	1000 W	1000 W	1000 W	1000 W	1000 W
Power	1 kW	1 kW	1 kW	1 kW	1 kW	1 kW
Amperage	4.3 A	4.3 A	4.3 A	4.3 A	4.3 A	4.3 A
Air Flow	163 m ³ /h	163 m ³ /h	163 m ³ /h	163 m ³ /h	163 m ³ /h	163 m ³ /h
Vacuum Pressure	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O
Sound Level	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)
Type of Power Outlet	European	European	UK	UK	Swiss	Swiss
Suction Inlet Port	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Filter Cleaning	None	None	None	None	None	None
Dust Recovery Tank	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L
Dry Recovery - Disposable Filter Bag	8 L	8 L	8 L	8 L	8 L	8 L
Length	41 cm	41 cm	41 cm	41 cm	41 cm	41 cm
Width	41 cm	41 cm	41 cm	41 cm	41 cm	41 cm
Height	56 cm	56 cm	56 cm	56 cm	56 cm	56 cm
Weight (Vacuum Only)	9 kg.	9 kg.	9 kg.	9 kg.	9 kg.	9 kg.
Cord Length	10 m	10 m	10 m	10 m	10 m	10 m
CR-1 ULPA	110760E	110760EP	110762B	110762BP	110762C	110762CP
Model Name	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
Tension	240 V	240 V	240 V	240 V	240 V	240 V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Phase	Single	Single	Single	Single	Single	Single
Wattage	1000 W	1000 W	1000 W	1000 W	1000 W	1000 W
Power	1 kW	1 kW	1 kW	1 kW	1 kW	1 kW
Amperage	4.3 A	4.3 A	4.3 A	4.3 A	4.3 A	4.3 A
Air Flow	163 m ³ /h	163 m ³ /h	163 m ³ /h	163 m ³ /h	163 m ³ /h	163 m ³ /h
Vacuum Pressure	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O
Sound Level	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)

Type of Power Outlet	Chinese	Chinese	European	European	UK	UK
Suction Inlet Port	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Filter Cleaning	None	None	None	None	None	None
Dust Recovery Tank	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L
Dry Recovery - Disposable Filter Bag	8 L	8 L	8 L	8 L	8 L	8 L
Length	41 cm	41 cm	41 cm	41 cm	41 cm	41 cm
Width	41 cm	41 cm	41 cm	41 cm	41 cm	41 cm
Height	56 cm	56 cm	56 cm	56 cm	56 cm	56 cm
Weight (Vacuum Only)	9 kg.	9 kg.	9 kg.	9 kg.	9 kg.	9 kg.
Cord Length	10 m	10 m	10 m	10 m	10 m	10 m
CR-1 ULPA	110762D	110762DP	110762E	110762EP		
Model Name	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA		
Type (Powerhead)	Electric	Electric	Electric	Electric		
Tension	240 V	240 V	240 V	240 V		
Frequency	50 Hz	50 Hz	50 Hz	50 Hz		
Phase	Single	Single	Single	Single		
Wattage	1000 W	1000 W	1000 W	1000 W		
Power	1 kW	1 kW	1 kW	1 kW		
Amperage	4.3 A	4.3 A	4.3 A	4.3 A		
Air Flow	163 m ³ /h	163 m ³ /h	163 m ³ /h	163 m ³ /h		
Vacuum Pressure	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O	2510 mm H ₂ O		
Sound Level	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)		
Type of Power Outlet	Swiss	Swiss	Chinese	Chinese		
Suction Inlet Port	38 mm	38 mm	38 mm	38 mm		
Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)		
Filter Cleaning	None	None	None	None		
Dust Recovery Tank	15.1 L	15.1 L	15.1 L	15.1 L		
Dry Recovery - Disposable Filter Bag	8 L	8 L	8 L	8 L		
Length	41 cm	41 cm	41 cm	41 cm		
Width	41 cm	41 cm	41 cm	41 cm		
Height	56 cm	56 cm	56 cm	56 cm		
Weight (Vacuum Only)	9 kg.	9 kg.	9 kg.	9 kg.		

Use only recommended tools & accessories

ULPA Filter for CR-1 ULPA - Included



Main Cloth Filter - Included



A complete tool kit is included (Part No. 323495)



A package of 5 synthetic recovery bags is included (Part No. 212500)



CR-1 ULPA with Stainless Steel Recovery Tank



#214860 HEPA/ULPA Filter Protector/Housing Kit - Available