

European Headquarters

Tiger-Vac Europa S.R.L. Via Marie Curie 17 Zona Industriale Ponte Rizzoli Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52) Fax: ((39) 051 4695077) Website: http://www.tiger-vac.eu Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc. 2020 Dagenais Blvd. Ouest Laval, Quebec Canada H7L 5W2

Tel: (450-625-0099) Fax: (450-625-3388) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com















Pharma Applications

Cleanroom Compatible

Wet and Dry Recovery

High Filtration Efficiency Unit Included

Static Dissipating











Activated Carbon

Stainless General

Accessories Included

Less than 10 ohms

EMI Shielded

Specifications For CWR MRAC SERIES

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank	Dry Recovery - Disposable Filter Bag
CWR- 10 (4W)	110520B	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	European	28.4 L	19 L
MRAC	Dimensions	Dimensions: H113 cm x W46 cm x L61 cm Weight: 44 kg. Sound Level: 75 dB(A)										
Description	Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											

CWR- 10 (4W)	110520C	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	UK	28.4 L	19 L
MRAC	Dimensions	: H113 cm	n x W46 cm	x L61 cm	Weight	: 44 kg.	Sound Lev	vel: 75 dB	(A)			
Description	Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											

CWR- 10 (4W)	110520D	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	Swiss	28.4 L	19 L
MRAC	Dimensions	: H113 cm	n x W46 cm	x L61 cm	Weight	: 44 kg.	Sound Lev	vel: 75 dB	(A)			
Description	escription: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											

CWR- 10 (4W)	110520E	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	Chinese	28.4 L	19 L
MRAC	Dimensions	: H113 cm	n x W46 cm	x L61 cm	Weight	: 44 kg.	Sound Lev	vel: 75 dB	(A)			
Description	on: Manufact	urer moto	r performand	e only on	an orifice	of Ø2" (Ø	50mm). Res	ults may v	ary.			

CWR- 15 (4W)	110524B	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	European	47.3 L	19 L
MRAC	Dimensions	: H122 cm	n x W46 cm	x L61 cm	Weight	: 45 kg.	Sound Le	vel: 75 dB	(A)			
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm), Results may vary.												

CWR- 15 (4W)	110524C	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	UK	47.3 L	19 L
MRAC	Dimensions	: H122 cm	n x W46 cm	x L61 cm	Weight	: 45 kg.	Sound Lev	vel: 75 dB	(A)			
Description	Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											

CWR- 15 (4W)	110524D	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	Swiss	47.3 L	19 L
MRAC	Dimensions	: H122 cm	n x W46 cm	x L61 cm	Weight	:: 45 kg.	Sound Lev	vel: 75 dB	(A)			
Description	on: Manufact	: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										

CWR- 15 (4W)	110524E	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	Chinese	47.3 L	19 L
MRAC	Dimensions	: H122 cm	n x W46 cm	k L61 cm	Weight	: 45 kg.	Sound Lev	/el: 75 dB	(A)			
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary												

CWR- 15 (4W)	110528B	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	European	47.3 L	19 L
POLY MRAC	Dimensions	: H122 cm	n x W46 cm	x L61 cm	Weight	: 45 kg.	Sound Le	vel: 75 dB	(A)			
Description	Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											
CWR- 15 (4W)	110528C	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	UK	47.3 L	19 L
POLY MRAC	Dimensions	: H122 cm	n x W46 cm	x L61 cm	Weight	: 45 kg.	Sound Le	vel: 75 dB	(A)			
Description	on: Manufact	urer moto	r performano	e only on	an orifice	of Ø2" (Ø	50mm). Res	ults may v	ary.			
CWR- 15 (4W)	110528D	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	Swiss	47.3 L	19 L
POLY MRAC	Dimensions	: H122 cm	n x W46 cm	x L61 cm	Weight	: 45 kg.	Sound Le	vel: 75 dB	(A)			
Description	on: Manufact	urer moto	r performand	e only on	an orifice	of Ø2" (Ø	50mm). Res	ults may v	ary.			
CWR- 15 (4W)	110528E	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m ³ /h	2180 mm H ₂ 0	Chinese	47.3 L	19 L
POLY MRAC	Dimensions	s: H122 cm	n x W46 cm	x L61 cm	Weight	: 45 kg.	Sound Le	vel: 75 dB	(A)			
Description	on: Manufact	urer moto	r performand	ce only on	an orifice	of Ø2" (Ø	50mm). Res	ults may v	ary.			

Please note that specifications are subject to change without notice

Technical Sheet For CWR MRAC SERIES

ULPA FI	LTER AND ACCESSORIES - Included
Part #	Description
211027	ULPA FILTER (U15)

HEPA FI	ILTER - INTERNAL - FOR USE WITH MIDDLE RING - Optional
Part #	Description
211027B	HEPA FILTER 99.995% EFFICIENCY ON 0.3 MICRON (CE VERSION)

FILTERS	FILTERS AND ACCESSORIES - Included								
Part #	Description								
211305	DOUBLE CLOTH FILTER ASSEMBLY								
211394A	LIQUID FILTER ASSEMBLY WITH STAINLESS STEEL RING								

DISPOSABLE FILTER BAGS FOR MODEL CWR-10 (4W) MRAC - Included	
Part #	Description
219028-5	SYNTHETIC RECOVERY BAGS (WHITE) FOR EMI CWR (PACKAGE OF 5)
211840	PVC PIPE CONNECTOR FOR PAPER FILTER BAG -STAINLESS STEEL TANK

DISPOSA	DISPOSABLE FILTER BAGS FOR MODEL CWR-15 (4W) MRAC - Included	
Part #	Description	
218063-5	SYNTHETIC RECOVERY BAGS, 10" x 28", 50mm COLLAR (PACKAGE OF 5))	
211841	PVC PIPE CONNECTOR FOR PAPER FILTER BAG -STAINLESS STEEL TANK	

DISPOSABLE FILTER BAGS FOR MODEL CWR-15 (4W) POLY MRAC - Included	
Part #	Description
218063-5	SYNTHETIC RECOVERY BAGS, 10" x 28", 50mm COLLAR (PACKAGE OF 5))
211282	PVC PIPE CONNECTOR FOR PAPER FILTER BAG

ACTIVAT	ACTIVATED CARBON CARTRIDGE - Optional	
Part #	Description	
212200B	CARBON CARTRIDGE ASSEMBLY WITH 3mm CARBON (REGULAR)	
212200C	CARBON CARTRIDGE ASSEMBLY WITH 3mm MERSORB ACTIVATED CARBON (FOR MERCURY VAPORS)	
212200K	CARBON CARTRIDGE ASSEMBLY WITH 3mm KOGC3/KINA3 CARBON (FOR CHLORIDE VAPORS)	
212200L	CARBON CARTRIDGE ASSEMBLY WITH 3mm A-3 CARBON (FOR ARSINE AND PHOSPHINE VAPORS)	

DRAIN HOSE FOR MODEL CWR-10/15 (4W) MRAC - Included

Part #	Description
381093	DRAIN HOSE ASSEMBLY 0.75"(19mm)x5'(1.5m)CLEAR HOSE WITH 0.75"(19mm) STAINLESS STEEL FEMALE CAMLOCK

DRAIN H	DRAIN HOSE FOR MODEL CWR-15 (4W) POLY MRAC - Included	
Part #	Description	
381092	DRAIN HOSE ASSEMBLY 0.75" x 5'(1.5m) CLEAR HOSE w/ 0.75"(19mm) PVC FEMALE CAMLOCK	

TOOLS	TOOLS AND ACCESSORIES FOR MODELS CWR-10/15 (4W) MRAC - Included	
Part #	Description	
323403	CLEAR URETHANE HOSE ASMBLY 1.25"(32mm)x10'(3m), w/1.5" S/S FEMALE CAMLOCK, WITH S/S CURVED HANDLE	
323330	EXTENSION WANDS, BOTH STRAIGHT, 1.25"(32mm) x 20.5"(52cm), STAINLESS STEEL (SET OF 2)	
323311	COMBI TOOL, 1.25"(32mm) x 10.5" (27cm), BEIGE, WITH HOLE FOR BUTTON LOCK	
323317	UTILITY FLOOR TOOL WITH WHEELS & WITH SQUEEGEE BLADES 1.25"(32mm) x 12"(30cm), BEIGE PLASTIC	
323321	ROUND TOOL, WITH RUBBER BLADES, Ø1.25"(32mm)	
323314	UPHOLSTERY FLAT TOOL, Ø1.25"(32mm), PVC	
323313	CREVICE TOOL, 1.25"(32mm) x 9"(23cm), BEIG, PVC	
211701	DEFOAMING LIQUID (BOTTLE) 909 ml(31 fl oz.)- FOR WET RECOVERY MODE ONLY	
211065	GROUND CONTINUITY TESTER	

TOOLS	TOOLS AND ACCESSORIES FOR MODEL CWR-15 (4W) POLY MRAC - Included	
Part #	Description	
323404	SUCTION HOSE ASSEMBLY,1.25"(32mm)x10'(3m)CLEAR URETHANE, ITH SS CURVED HANDLE&PLASTIC FEMALE CAMLOCK	
323330	EXTENSION WANDS, BOTH STRAIGHT, 1.25"(32mm) x 20.5"(52cm), STAINLESS STEEL (SET OF 2)	
323311	COMBI TOOL, 1.25"(32mm) x 10.5" (27cm), BEIGE, WITH HOLE FOR BUTTON LOCK	
323317	UTILITY FLOOR TOOL WITH WHEELS & WITH SQUEEGEE BLADES 1.25"(32mm) x 12"(30cm), BEIGE PLASTIC	
323321	ROUND TOOL, WITH RUBBER BLADES, Ø1.25"(32mm)	
323314	UPHOLSTERY FLAT TOOL, Ø1.25"(32mm), PVC	
323313	CREVICE TOOL, 1.25"(32mm) x 9"(23cm), BEIG, PVC	
211701	DEFOAMING LIQUID (BOTTLE) 909 ml(31 fl oz.)- FOR WET RECOVERY MODE ONLY	
211065	GROUND CONTINUITY TESTER	

NEEDLE TRAP AND ACCESSORIES - Optional	
Part #	Description
215500	NEEDLE TRAP ASSEMBLY, STAINLESS STEEL, 2"(50mm) INLET X 1.25"(32mm) OUTLET, ELECTROPOLISHED
500235M	TIGER-CLAW ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x4.5"(11.5cm)
500231M	CONICAL NOZZLE ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x7.5"(19cm)