



Meets EU Safety, Health and Environmental Protection Requirements

Characteristics



SD Accessories - Included



HEPA - Included



High Filtration Efficiency Unit




Dry Recovery




Coalescing Filter Element



Stainless General



Wet Mix - Water



3D Printing



- For the safe collection of combustible dusts in ordinary locations/areas and unclassified zones
- Protected against ingress of dust IP5X
- Very high level of protection inside the collection tank
- Ignition source safe/protected
- Dual HEPA filters H14 (upstream and downstream)
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency at 0.3 micron
- Longer life brushless motor available. Always with 2 x H14 HEPA filters
- Filter blockage indicator light
- Recovery capacity of 11 lb (5 kg) of dust into 6.5 gal. (25L) of water (no oil)
- Brushless motor available

Specifications

2D-15 (IT-63L) CFE HEPA ORDLOC SERIES W/3D TOOL KIT	113187B-3D
Model Name	2D-15 (IT-63L) CFE HEPA ORDLOC SERIES
Type (Powerhead)	Electric
Tension	220-240 V
Frequency	50/60 Hz
Phase	Single
Wattage	1200 W
Power	1.2 kW
Amperage	5 A
Air Flow	194 m³/h
Vacuum Pressure	2504 mm H ₂ O
Sound Level	75 dB(A)
Type of Power Outlet	Not Included
Suction Inlet Port	50 mm
Cart Type	Detachable Tank (DT)
Filter Cleaning	Liquid Immersion Bath
Length	79 cm
Width	61 cm
Height	160 cm
Weight (Vacuum Only)	82 kg.
Cord Length	10 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



2D-15 (IT-63L) with Recovery Tank removed



Liquid Level Indicator Tube - Included



Mist Arrestor Pack - Optional



Coalescing HEPA filter (Upstream) - Included



Sieve Basket - Included



Cone for Interceptors - Included



3D Tool Kit for 2" camlock suction inlet - included



Optional 3D Tools



Degassing Vent - Included