

ATEX

CE II 2GD
Ex h IIC T6 Gb
Ex h IIIC T85°C Db



GUARANTEED for the Safe Recovery of Combustible/Conductive Dusts


ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Characteristics



EX Certified



Less than 10 ohms



Dry Recovery



HEPA - Included



High Filtration Efficiency Unit



SS 304



3D Printing

- Static dissipating and conductive
- Ideal for Medical/Dental 3D printer cleaning and maintenance
- Includes a complete static dissipative tool kit
- Low noise level - only 68 dB(A)
- Pressure regulator included. Pressure regulator is adjustable between 0 psi. (0 bar) to 150 psi. (10 bars). It is factory set at 80 psi. (5.5 bars) for ideal performance and noise level

Specifications

| ATEX-10A (40L) HEPA W/3D TOOL KIT | 113115 |
|-----------------------------------|---------------------------------|
| Model Name | ATEX-10A (40L) HEPA MINI SERIES |
| Type (Powerhead) | Pneumatic |
| Venturi | Single |
| Minimum Compressor | 15 HP |
| Air Line Size (Diam.) | 1/2" (12.7mm) |
| Input Air Volume | 16.5-21.2 L/s |
| Input Air Pressure | 5.5 Bar |
| Air Flow | 187 m ³ /h |
| Vacuum Pressure | 2790 mm H ₂ O |
| Sound Level | 68 dB(A) |
| Suction Inlet Port | 38 mm |
| Cart Type | 4 Wheel Dolly (4W) |
| Length | 48 cm |
| Width | 46 cm |
| Height | 86 cm |

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



3D Tool Kit for 60 mm suction inlet - included



Optional 3D Tools



Pressure Regulator - Included