



CE EX II 3D  
Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X  
LCIE 19 ATEX 1001 X




IECEX 3rd Party Certified  
Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X  
IECEX LCIE 15.0048

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



### Characteristics



- Legally certified dust ignition protected by an OSHA approved Nationally Recognized Testing Laboratory (NRTL)
- Immersion separator "Wet Mix". For use with water (no oil)
- Designed for the recovery and INERTIZATION of combustible dust into a liquid immersion bath
- Meets the requirements for a Liquid Precipitation Collector for metal dusts as outlined in NFPA 484
- Electric
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency at 0.3 micron
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 4 x H14 HEPA filters
- Stainless steel Type 304 interceptor tank
- Recovery capacity of 11 lb (5 kg) of dust into 6.5 gal. (25L) of water (no oil)
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Degassing vent allows gas to be evacuated automatically from the unit
- Equipped with a liquid level indicator
- Includes a complete static dissipative tool kit

## Specifications

C-10 EX (IT-63L) CFE HEPA W/3D TOOL KIT	113172B-3D	113172B-BL3D
<b>Model Name</b>	C-10 EX (IT-63L) CFE HEPA W/3D TOOL KIT	C-10 EX (IT-63L) CFE HEPA BLSD W/3D TOOL KIT
<b>Type (Powerhead)</b>	Electric	Electric
<b>Tension</b>	220-240 V	220-240 V
<b>Frequency</b>	50/60 Hz	50/60 Hz
<b>Phase</b>	Single	Single
<b>Wattage</b>	1200 W	1100 W
<b>Power</b>	1.2 kW	1.1 kW
<b>Amperage</b>	5 A	8 A
<b>Air Flow</b>	194 m <sup>3</sup> /h	215 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	2504 mm H <sub>2</sub> O	2250 mm H <sub>2</sub> O
<b>Sound Level</b>	72 dB(A)	72 dB(A)
<b>Type of Power Outlet</b>	Not Included	Not Included
<b>Suction Inlet Port</b>	50 mm	50 mm
<b>Cart Type</b>	Detachable Tank (DT)	Detachable Tank (DT)
<b>Filter Cleaning</b>	None	None
<b>Length</b>	cm	cm
<b>Width</b>	cm	cm
<b>Height</b>	cm	cm
<b>Cord Length</b>	10 m	10 m

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



3D Tool Kit for 2" camlock suction inlet - included



Optional 3D Tools



Liquid Level Indicator Tube - Included



Mist Arrester Pack - Included



C-10EX (IT-63L) CFE SK HEPA with Recovery Tank removed



Coalescing HEPA filter (Upstream) - Included



Sieve Basket - Included



Cable Holder Hook included on the side of the powerhead



Longer Life Brushless Motor Available (always with 4 x H14 HEPA filters)



Degassing Vent - Included