

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)




CE EX II 3D  
Ex h t c III C T200°C (T85°C for BLSD version)  
Dc IP6X  
LCIE 19 ATEX 1001 X



IECEx 3rd Party Certified  
Ex h t c III C T200°C (T85°C for BLSD version)  
Dc IP6X  
IECEx LCIE 15.0048



EX Certified



Less than 10 ohms



HEPA - Included



High Filtration Efficiency Unit




Coalescing Filter Element




Dry Recovery



SS 304




Wet Mix - Water



Wet Mix - Oil



SD Accessories - Included



3D Printing



Brushless Motor Available

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

### Specifications For C-10 EX (IT-40L) DT (CFE) HEPA W/3D TOOL KIT

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet
C-10 EX (IT-40L) DT (CFE) HEPA W/3D TOOL KIT	113179B-3D	220-240 V	50/60 Hz	Single	1200 W	1.2 kW	5 A	194 m <sup>3</sup> /h	2504 mm H <sub>2</sub> O	Not Included
	Dimensions: H137 cm x W56 cm x L66 cm    Weight: 42 kg.    Sound Level: 72 dB(A)									
C-10 EX (IT-40L) DT (CFE) HEPA BLSD W/3D TOOL KIT	113179B-BL3D	220-240 V	50/60 Hz	Single	1100 W	1.1 kW	8 A	215 m <sup>3</sup> /h	2250 mm H <sub>2</sub> O	Not Included
	Dimensions: H137 cm x W56 cm x L66 cm    Weight: 42 kg.    Sound Level: 72 dB(A)									
Description: With Brushless Motor										

Please note that specifications are subject to change without notice

### Technical Sheet For C-10 EX (IT-40L) DT (CFE) HEPA W/3D TOOL KIT

HEPA FILTERS - Included	
Part #	Description
215372	HEPA FILTER WITH GASKETS ON BOTH SIDES, 99.99% ON 0.3 MICRON, 11.522" OD x 9.066" ID x 2" HIGH
211854	HEPA FILTER (H14) WITH GASKET, 2"(50mm) HIGH
COALESCING FILTER ELEMENT - Included	
Part #	Description
215792A-HEPA	REPLACEMENT COALESCING FILTER ELEMENT, HEPA GRADE, 4.75" HIGH, w/NITRILE GASKET #219259-04
MIST ARESTOR PACK - Included	
Part #	Description
218282	MIST ARRESTOR SCREENS, MADE OF ALUMINUM MESH, FOR IT-40L (SET OF 6 SCREENS)

218284	MIST ARRESTOR PACK ASSEMBLY (ALUMINUM SCREENS WITH STAINLESS STEEL MESH)
--------	--

<b>CONDUCTIVE RECOVERY BAG - Included</b>	
---	--

Part #	Description
219992A	CONDUCTIVE RECOVERY BAG FOR IT-40L MINI ENHANCED
219992	CONDUCTIVE RECOVERY BAG FOR IT-40L MINI ENHANCED (PACKAGE OF 3)

<b>DEPRESSOR CAGE FOR CONDUCTIVE RECOVERY BAG - Optional</b>	
--	--

Part #	Description
228093	DEPRESSOR CAGE FOR CONDUCTIVE WET RECOVERY BAG FOR IT-40L, MADE OF TYPE 304 STAINLESS STEEL

<b>TOOLS AND ACCESSORIES - Included</b>	
---	--

Part #	Description
383440	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASSEMBLY 1.5"(38mm) x 10'(3m) FOR 1.5" CAMLOCK INTAKE
381818	CREVICE TOOL 1.5"(38mm) x 8"(20cm) w/1.5" ALUMINUM TUBE, BLACK RUBBER, CONDUCTIVE & OIL RESISTANT
383312A	ROUND BRUSH ASSEMBLY, ESD SAFE PLASTIC, FOR USE WITH 1.5" (38mm) HOSE
383462	CONICAL NOZZLE ASMBLY w/CURVED TIP, 10"(25cm) CONDUCTIVE RUBBER, PRESSURE FIT (323562+381155A-H)

<b>TOOLS AND ACCESSORIES - Optional</b>	
---	--

Part #	Description
381477	DOUBLE BEND WAND (2pc) 1.5" (38mm) x 54" (137cm), CHROME, w/TAPER FOR PLASTIC FLOOR TOOLS
381448A	UTILITY FLOOR TOOL, Ø1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES