C-10 EX (IT-63L) CFE SK HEPA FOR HAZLOCS

Automotive/Aerospace - Dust Extraction/Vacuum Sanding Kit System



The name to vacuum with

ATEX

CE EX II 3D

Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X LCIE 19 ATEX 1001 X

IEC TECEX

IECEx 3rd Party Certified

Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X **IECEx LCIE 15.0048**

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Characteristics













ess than 10

Wet Mix - Water

Included

High Filtration Efficiency Unit

Coalescing







Motor Available

Sanding kit systems

- Legally certified dust ignition protected by an OSHA approved Nationally Recognized Testing Laboratory (NRTL)
- Immersion separator "Wet Mix". For use with water
- Designed for the recovery and INERTIZATION of combustible dust into a liquid immersion bath
- Meets the requirements for a Liquid Precipitation Collector for metal dusts as outlined in NFPA 484
- Electric
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency at 0.3
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 4 x H14 HEPA filters
- Stainless steel Type 304 interceptor tank
- Recovery capacity of 11 lb (5 kg) of dust into 6.5 gal. (25L) of water (no oil)
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Degassing vent allows gas to be evacuated automatically from the unit
- Equipped with a liquid level indicator
- Fully automatic remote start/stop system allows the vacuum system to be controlled by pneumatic hand tools
- Portable and equipped with a single, or dual, static dissipative suction hose connector

Specifications

| C-10 EX (IT-63L) CFE SK HEPA FOR HAZLOCS | 113174B |
|--|------------------------------|
| Model Name | C-10 EX (IT-63L) CFE SK HEPA |
| Type (Powerhead) | Electric |
| Tension | 220-240 V |
| Frequency | 50/60 Hz |
| Phase | Single |
| Wattage | 1200 W |
| Power | 1.2 kW |
| Amperage | 5 A |
| Air Flow | 194 m ³ /h |
| Vacuum Pressure | 2504 mm H ₂ 0 |
| Sound Level | 72 dB(A) |
| Type of Power Outlet | European |
| Suction Inlet Port | 50 mm |
| Cart Type | Detachable Tank (DT) |
| Filter Cleaning | None |
| Cord Length | 10 m |

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Liquid Level Indicator Tube - Included



Sieve Basket - Included



Coalescing HEPA filter (Upstream) - Included



Wye Connector - Included



Mist Arrester Pack - Included



Suction/Airline Hose Assembly, Static Dissipative and Conductive - Included



C-10EX (IT-63L) CFE SK HEPA with Recovery Tank removed



Cable Holder Hook included on the side of the powerhead



Longer Life Brushless Motor Available (always with 4 x H14 HEPA filters)



Degassing Vent - Included