



CE EX II 3D
Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X
LCIE 19 ATEX 1001 X




IECEx 3rd Party Certified
Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X
IECEx LCIE 15.0048

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)




Characteristics



Less than 10 ohms



Dry Recovery



Wet Mix - Water



HEPA - Included



High Filtration Efficiency Unit



SS 304



Coalescing Filter Element



Detachable Tank



EX Certified



Brushless Motor Available

- Sanding kit systems
- Legally certified dust ignition protected by an OSHA approved Nationally Recognized Testing Laboratory (NRTL)
- Immersion separator "Wet Mix". For use with water (no oil)
- Designed for the recovery and INERTIZATION of combustible dust into a liquid immersion bath
- Meets the requirements for a Liquid Precipitation Collector for metal dusts as outlined in NFPA 484
- Electric
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency at 0.3 micron
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 4 x H14 HEPA filters
- Stainless steel Type 304 interceptor tank
- Recovery capacity of 11 lb (5 kg) of dust into 6.5 gal. (25L) of water (no oil)
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Degassing vent allows gas to be evacuated automatically from the unit
- Equipped with a liquid level indicator
- Fully automatic remote start/stop system allows the vacuum system to be controlled by pneumatic hand tools
- Portable and equipped with a single, or dual, static dissipative suction hose connector

Specifications

C-10 EX (IT-63L) CFE SK HEPA FOR HAZLOCS	113174B
Model Name	C-10 EX (IT-63L) CFE SK HEPA
Type (Powerhead)	Electric
Tension	220-240 V
Frequency	50/60 Hz
Phase	Single
Wattage	1200 W
Power	1.2 kW
Amperage	5 A
Air Flow	194 m ³ /h
Vacuum Pressure	2504 mm H ₂ O
Sound Level	72 dB(A)
Type of Power Outlet	European
Suction Inlet Port	50 mm
Cart Type	Detachable Tank (DT)
Filter Cleaning	None
Cord Length	10 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Liquid Level Indicator Tube - Included



Sieve Basket - Included



Coalescing HEPA filter (Upstream) - Included



Wye Connector - Included



Mist Arrester Pack - Included



Suction/Airline Hose Assembly, Static Dissipative and Conductive - Included



C-10EX (IT-63L) CFE SK HEPA with Recovery Tank removed



Cable Holder Hook included on the side of the powerhead



Longer Life Brushless Motor Available (always with 4 x H14 HEPA filters)



Degassing Vent - Included