

Characteristics



HEPA -
Included



High Filtration
Efficiency Unit



Dry Recovery



Accessories
Included



SS 430



Low Noise



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Designed for the recovery of asbestos, lead, mold, etc.
- Lightweight and portable
- Heavy duty 2-stage by-pass motor
- Equipped with a 3-stage filtration system
- For dry recovery only
- Heavy duty plastic recovery tank
- Stainless steel recovery tank available
- Ready to use - filters and tool kit included
- 4-wheel cart for easy maneuverability
- Built-in storage tray with two large 6.75" (170 mm) rear wheels and two 2.25" (60 mm) front wheels
- 50' grounded power cord available

Specifications

AS-400 HEPA (Dry)	110765B	110765C	110765D	110765E	110766B	110766C
Model Name	AS-400 HEPA WITH STAINLESS STEEL TANK	AS-400 HEPA WITH STAINLESS STEEL TANK	AS-400 HEPA WITH STAINLESS STEEL TANK	AS-400 HEPA WITH STAINLESS STEEL TANK	AS-400 HEPA WITH POLY TANK	AS-400 HEPA WITH POLY TANK
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
Tension	220-240 V	220-240 V	220-240 V	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Phase	Single	Single	Single	Single	Single	Single
Wattage	1200 W	1200 W	1200 W	1200 W	1200 W	1200 W
Power	1.2 kW	1.2 kW	1.2 kW	1.2 kW	1.2 kW	1.2 kW
Amperage	5 A	5 A	5 A	5 A	5 A	5 A
Air Flow	194 m ³ /h	194 m ³ /h	194 m ³ /h	194 m ³ /h	194 m ³ /h	194 m ³ /h
Vacuum Pressure	2504 mm H ₂ O	2504 mm H ₂ O	2504 mm H ₂ O	2504 mm H ₂ O	2504 mm H ₂ O	2504 mm H ₂ O
Sound Level	63 dB(A)	63 dB(A)	63 dB(A)	63 dB(A)	63 dB(A)	63 dB(A)
Type of Power Outlet	European	UK	Swiss	Chinese	European	UK
Suction Inlet Port	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
Cart Type	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	None	None	None	None	None	None
Dust Recovery Tank	38 L	38 L	38 L	38 L	38 L	38 L
Dry Recovery - Disposable Filter Bag	38 L	38 L	38 L	38 L	38 L	38 L
Length	50 cm	50 cm	50 cm	50 cm	50 cm	50 cm
Width	52 cm	52 cm	52 cm	52 cm	52 cm	52 cm
Height	84 cm	84 cm	84 cm	84 cm	84 cm	84 cm
Weight (Vacuum Only)	15 kg.	15 kg.	15 kg.	15 kg.	15 kg.	15 kg.
Cord Length	10 m	10 m	10 m	10 m	10 m	10 m
AS-400 HEPA (Dry)	110766D	110766E				
Model Name	AS-400 HEPA WITH POLY TANK	AS-400 HEPA WITH POLY TANK				
Type (Powerhead)	Electric	Electric				
Tension	220-240 V	220-240 V				
Frequency	50/60 Hz	50/60 Hz				
Phase	Single	Single				
Wattage	1200 W	1200 W				
Power	1.2 kW	1.2 kW				
Amperage	5 A	5 A				
Air Flow	194 m ³ /h	194 m ³ /h				

Vacuum Pressure	2504 mm H ₂ O	2504 mm H ₂ O
Sound Level	63 dB(A)	63 dB(A)
Type of Power Outlet	Swiss	Chinese
Suction Inlet Port	38 mm	38 mm
Cart Type	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	None	None
Dust Recovery Tank	38 L	38 L
Dry Recovery - Disposable Filter Bag	38 L	38 L
Length	50 cm	50 cm
Width	52 cm	52 cm
Height	84 cm	84 cm
Weight (Vacuum Only)	15 kg.	15 kg.
Cord Length	10 m	10 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



AS-400 Disposable Filter Bags (Included) and Poly Liner Recovery Bags (Optional)



AS-400 HEPA (DRY) Tools and Accessories - Included



Beater Bar - Optional