

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Static Dissipating



HEPA - Included



High Filtration Efficiency Unit



Stainless General



SD Accessories - Included



Dry Recovery



Detachable Tank



CE II 2GD
Ex h IIC T6 Gb
Ex h IIIC T85°C Db



CE II 1/2 GD
External : Ex h IIC T6 Gb Ex h IIIC T85°C Db
Internal : Ex h IIC T6 Ga Ex h IIIC T50°C Da
-5°C ≤ Ta ≤ +37°C

EN 17348 DT - Combustible dust collection

Specifications For AVSD-57L (DT) MFS HEPA

Name	Part Number	Air Flow	Vacuum Pressure	Dust Recovery Tank
AVSD-57L (DT)MFS HEPA	112052	204 m ³ /h	4570 mm H ₂ O	55 L
	Dimensions: H130 cm x W64 cm x L64 cm Weight: 43 kg. Sound Level: 73 dB(A)			
Description: Specifications may vary depending upon performance of the compressor.				

Please note that specifications are subject to change without notice

Technical Sheet For AVSD-57L (DT) MFS HEPA

HEPA FILTER - Included

Part #	Description
219212	INTERNAL (UPSTREAM) HEPA FILTER ASSEMBLY FOR CD/EUR-36, 99.995% ON 0.3 MICRON

FILTERS - Included

Part #	Description
218638	SPECIAL MAIN FILTER ASSEMBLY, SD* PTFE STAR SHAPED (8) FILTER (PLEATED)

TOOLS AND ACCESSORIES - Included

Part #	Description
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
211029D	AIR SUPPLY HOSE ASSEMBLY SD*, 0.5" x 25' w/ONE FEMALE QUICK DISC. & w/0.5" MALE NPT ON OTHER END
381163	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5" (38mm) x 54" (137cm), CHROME w/ALUMINUM TOOL COUPLING
381377A	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH CONDUCTIVE BRISTLES
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM

TOOLS AND ACCESSORIES - Optional

Part #	Description
383438-50	CRUSHPROOF SUCTION HOSE, BLACK STATIC CONDUCTIVE (NO WIRE),Ø1.5" (Ø38mm) x 50'
383434	HOSE CUFF UNION WITH SWIVEL Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383436	HOSE CUFF Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383435	EXPANDER HOSE CUFF, 1.5"(38mm) HOSE TO 2"(50mm) TUBE, STATIC CONDUCTIVE, BLACK
500175	CAMLOCK SPECIAL PART C Ø2"(50mm)FEMALE ADAPTOR TO Ø1.5"(38mm)HOSE SHANK -ALUMINUM