

...The name to vacuum with

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS
All the electrical components are certified by an NRTL such as UL, CSA or ETL



Three Motors



HEPA - Included



High Filtration Efficiency Unit



Dry Recovery



Detachable Tank



SS 304



SD Accessories - Included

Specifications For TV-200 / TV-200S (DT) MFS HEPA ORDLOC SERIES

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet
TV-200 (DT) MFS HEPA ORDLOC-652	112060B-652	230 V	50/60 Hz	Single	3600 W	3.6 kW	15.8 A	630 m ³ /h	2790 mm H ₂ O	Not Included
	Dimensions: H138 cm x W66 cm x L81 cm Weight: 65 kg. Sound Level: 76 dB(A)									
Description: 60L (16 Gal.) Tank										
TV-200S (DT) MFS HEPA ORDLOC-652	112062B-652	230 V	50/60 Hz	Single	3600 W	3.6 kW	15.8 A	630 m ³ /h	2790 mm H ₂ O	Not Included
	Dimensions: H156 cm x W66 cm x L81 cm Weight: 70 kg. Sound Level: 76 dB(A)									

Please note that specifications are subject to change without notice

Technical Sheet For TV-200 / TV-200S (DT) MFS HEPA ORDLOC SERIES

FILTERS - Included	
Part #	Description
214079	HEPA FILTER CARTRIDGE, 8340 cm sq D.380mm x 320mm x 116mm H. MINIMUM EFFICIENCY 99.97% ON 0.3 MICRON
214057	CONDUCTIVE STAR SHAPED POLYESTER MAIN FILTER ASSEMBLY WITH RING

SUCTION HOSE - Included	
Part #	Description
500540C	CRUSHPROOF SUCTION HOSE ASMBLY, STATIC CONDUCTIVE, 2"(50mm) x 15'(4.5m),FOR PLANET 70mm INLET

TOOL KIT - Included	
Part #	Description
500108	2" (50mm) STATIC CONDUCTIVE TOOL KIT

EXTENSION HOSE - Optional	
Part #	Description
500540E2	STATIC CONDUCTIVE CRUSHPROOF EXTENSION HOSE 2"(50mm) x 15'(4.5m) w/2" UNION CUFF (500538+500537)