

ATEX

ATEX 1st Party Certified  
CE II 3D  
Ex tc IIIB T160°C Dc IP54



## Characteristics



- Ideal for the recovery of bulky and lightweight scrap materials
- Can be connected to process machines
- Continuous duty single phase or 3-phase (TEFC) motor. This induction motor does not contain normally arcing components
- Sight glass installed to monitor collection bag capacity
- For dry recovery only
- Powder coated steel construction. Stainless steel Type 304 available upon request
- 4 wheels for easy maneuverability

## Specifications

SRV-55	111550B1	111554B1
Model Name	SRV-55	SRV-55
Type (Powerhead)	Electric	Electric
TEFC Motor	Yes	Yes
Tension	400 V	400 V
Frequency	50 Hz	50 Hz
Phase	Three	Three
Wattage	2200 W	4000 W
Power	2.2 kW	4 kW
Amperage	5.6 A	8 A
Air Flow	335 m <sup>3</sup> /h	340 m <sup>3</sup> /h
Vacuum Pressure	3300 mm H <sub>2</sub> O	3560 mm H <sub>2</sub> O
VRV Setting	mm H <sub>2</sub> O	mm H <sub>2</sub> O
Type of Power Outlet	Not Included	Not Included
Suction Inlet Port	50 mm	50 mm
Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Filter Cleaning	None	None
Dust Recovery Tank	98.4 L	98.4 L
Width	64 cm	64 cm
Height	105 cm	105 cm
Weight (Vacuum Only)	59 kg.	75 kg.
Cord Length	10 m	10 m

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories