

## 4D-55L (DT) MFS HEPA ORDLOC SERIES

**Technical Sheet** 

**European Headquarters** 

Tiger-Vac Europa S.R.L. Via Marie Curie 17 Zona Industriale Ponte Rizzoli Ozzano Emilia, BO 40064 Tel: ((39) 051 79.53.52) Fax: ((39) 051 4695077) Website: http://www.tiger-vac.eu Email: info@tiger-vac.it International Headquarters

Tiger-Vac International Inc. 2020 Dagenais Blvd. Ouest Laval, Quebec Canada H7L 5W2 Tel: (450-625-0099) Fax: (450-625-3388) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com





Meets EU Safety, Health and Environmental Protection Requirements







SD Tools & Accessories



HEPA -



Dry Recovery

High Filtration

Efficiency Unit



Dual Motor

## **Specifications For 4D-55L (DT) MFS HEPA ORDLOC SERIES**

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
4D-55L (DT) MFS HEPA ORDLOC SERIES	112111B	240 V	50 Hz	Single	2100 W	2.1 kW	10 A	375 m <sup>3</sup> /h	2180 mm H <sub>2</sub> 0	Not Included	55 L

Please note that specifications are subject to change without notice

## Technical Sheet For 4D-55L (DT) MFS HEPA ORDLOC SERIES

HEPA FILTER - Included			
Part #	Description		
215373A-	HEPA FILTER, 99.99% EFFICIENCY ON 0.3 MICRON, ASSEMBLED WITH PLATE AND NO U-CHANNEL GASKET		
01			

FILTERS AND ACCESSORIES - Included				
Part #	Description			
218627	MAIN FILTER ASSEMBLY, PTFE FILTER *SD*			

POLY LINER RECOVERY BAGS AND ACCESSORIES - Included			
Part #	Description		
212100S	CONDUCTIVE POLY LINER WITH DRAW STRING (40 LITRES/10 GALLONS)		
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)		

TOOLS AND ACCESSORIES - Included		
Part #	Description	
500540	CRUSHPROOF SUCTION HOSE ASMBLY 2"(50mm) x15'(4.5m) STATIC CONDUCTIVE w/2"(50mm) FEMALE CAMLOCK (ALUM	
500160	WAND ONLY, SINGLE BEND, 2"(50mm) x 48" (122cm), ALUMINUM, WITH TAPER FOR FLOOR TOOL	
500161A	UNIVERSAL TOOL Ø2"(50mm)x20"(51cm)SD* NO COUPLING WITH BRASS WHEELS&CONDUCTIVE BRISTLES&RUBBER BLADE	
501184A	DUSTING BRUSH ALUMINUM SD* Ø2"(50mm)x5"(12.7cm)WITH CONDUCTIVE BRISTLES & TUBE FOR PRESSURE FIT	