CE

Meets EU Safety, Health and Environmental Protection Requirements



Characteristics











Stainless

High Filtration Efficiency Unit

Protected against ingress of dust

- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- PCS "Personal Cleaning Station" with small footprint intended to be wall mounted
- Ideal for locker rooms, changing rooms and gowning rooms
- Employees can remove (vacuum) dust and powder from their clothing before or after their shift
- Can also be removed from wall and used as a portable HEPA vac
- Heavy duty 2-stage by-pass motor
- For dry recovery only
- Stainless steel tank Type 430 fits any application
- Includes a static dissipative suction hose and round brush. Other static dissipative accessories are available as optional

Specifications

2D-1 (PCS-WM) HEPA ORDLOC SERIES	113386B
Model Name	2D-1 (PCS-WM) HEPA ORDLOC SERIES
Sound Level	75 dB(A)
Suction Inlet Port	38 mm
Dry Recovery - Disposable Filter Bag	8 L
Length	37 cm
Width	46 cm
Height	61 cm
Weight (Vacuum Only)	11 kg.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Can be removed from wall and used as a portable HEPA vac



2D-1 (PCS-WM) HEPA Cable Holder Hook included on the side of the powerhead



2D-1 (PCS-WM) HEPA Tool Hook also included