



ATEX 3rd Party Certified
CE II 2GD
Ex h IIC T6 Gb
Ex h IIC T85°C Db
LCIE 03 ATEX 6310 X



Ex h IIC T6 Gb
Ex h IIC T85°C Db
IECEX LCIE 17.0076 X



GUARANTEED for the Safe Recovery of Combustible/Conductive Dusts


ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Characteristics



EX Certified



Less than 10 ohms



HEPA - Included



Dry Recovery



High Filtration Efficiency Unit



SS 304



Accessories Included

- Legally certified explosion proof/dust ignition proof
- Less than 10 ohms of resistivity
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Designed for point of generation dust control
- Up to 2 operators working simultaneously
- Pneumatic (air-operated)
- For dry recovery only
- All stainless steel Type 304 construction
- Mounted on a 4-wheel dolly for easy maneuverability. Dolly has static dissipative wheels
- Complete system includes all sanders, hoses, abrasives start-up kit and filters to ensure turn-key operation
- Abrasives are available in PSA (sticky), Hook & Loop (Velcro®), or Screen Type
- Many different grits are available

Specifications

SS-10 (4W) SK HEPA	110263	110264A	110264B	110264C	110264D	110264E
Model Name	SS-10 (4W) SK HEPA - VACUUM ONLY	SS-10 (4W) SK HEPA - 5" PSA (STICKY)	SS-10 (4W) SK HEPA - 5" VELCRO	SS-10 (4W) SK HEPA - 6" PSA (STICKY)	SS-10 (4W) SK HEPA - 6" VELCRO	SS-10 (4W) SK HEPA - 5" SCREEN TYPE
Type (Powerhead)	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic
Venturi	Single	Single	Single	Single	Single	Single
Venturi (diam.)	6 mm	6 mm	6 mm	6 mm	6 mm	6 mm
Minimum Compressor	15-25 HP	15-25 HP	15-25 HP	15-25 HP	15-25 HP	15-25 HP
Air Line Size (Diam.)	1/2" (12.7mm)	1/2" (12.7mm)	1/2" (12.7mm)	1/2" (12.7mm)	1/2" (12.7mm)	1/2" (12.7mm)
Input Air Volume	21.2 L/s	21.2 L/s	21.2 L/s	21.2 L/s	21.2 L/s	21.2 L/s
Input Air Pressure	5.5 Bar	5.5 Bar	5.5 Bar	5.5 Bar	5.5 Bar	5.5 Bar
Air Flow	204 m ³ /h	204 m ³ /h	204 m ³ /h	204 m ³ /h	204 m ³ /h	204 m ³ /h
Vacuum Pressure	4570 mm H ₂ O	4570 mm H ₂ O	4570 mm H ₂ O	4570 mm H ₂ O	4570 mm H ₂ O	4570 mm H ₂ O
Suction Inlet Port	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Filter Cleaning	None	None	None	None	None	None
Dry Recovery - Disposable Filter Bag	19 L	19 L	19 L	19 L	19 L	19 L
SS-10 (4W) SK HEPA	110264F					
Model Name	SS-10 (4W) SK HEPA - 6" SCREEN TYPE					
Type (Powerhead)	Pneumatic					
Venturi	Single					
Venturi (diam.)	6 mm					
Minimum Compressor	15-25 HP					
Air Line Size (Diam.)	1/2" (12.7mm)					
Input Air Volume	21.2 L/s					
Input Air Pressure	5.5 Bar					
Air Flow	204 m ³ /h					
Vacuum Pressure	4570 mm H ₂ O					
Suction Inlet Port	38 mm					

Cart Type	4 Wheel Dolly (4W)
Filter Cleaning	None
Dry Recovery - Disposable Filter Bag	19 L

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Main Cloth Filter, Static Dissipative - Included



Disposable Filter Bag - Included



HEPA Filter - Included



Air Supply Hose Assembly, Static Dissipative and Conductive - Included



Multimeter - Included



Suction/Airline Hose Assembly, Static Dissipative and Conductive - Included



Wye Connector - Included